



INDUSTRIAL TUMBLE-DRYER

IDR250

12 KG

IDR285

16 KG

IDR345

19 KG

FEATURES

- Standard galvanized drum with large diameter
- Easy-to-use microprocessor (ECT)
- Combination of radial and axial airflow
 - maximal heat transfer
 - low energy consumption
 - short drying time
- Large door opening for easy loading and unloading
- Self cleaning lint screen

OPTIONS

- Coin operated version
- Stainless steel drum
- Reverse drum
- Flex Control Programmer (FCT)
- Residual moisture control
 - safe drying of delicate linen
 - humidity detection in %
 - ideal in combination with Softwash®
 - Ideal for dry cleaners, fire departments
 - available on Easy and Flex Control
- Stainless steel front
- Wireless communication with cloud-based systems (WiFi kit - to order through Accessories)



LARGE DOOR
OPENING



ENERGY
EFFICIENT

YOUR SMART LAUNDRY PARTNER

	IDR250	IDR285	IDR345
DRUM			
CAPACITY 1:18 (KG)	12	16	19
CAPACITY 1:22 (KG)	11	13	16
VOLUME (L)	250	285	345
DIAMETER (MM)	Ø760		Ø760
NUMBER OF DRUMS	1		1
NUMBER OF LOADING DOORS	1		1
DRYING PERFORMANCE			
AIRFLOW (M ³ /H)	520	550	600
DRYING AVERAGE (L/MIN)	0,166 (EL) / 0,187 (G)	0,206 (EL) / 0,223 (G)	0,260 (EL) / 0,270 (G)
GAS HEATING			
GAS CONNECTION (IN)	1/2"		1/2"
ELECTRICAL CONNECTION - gas heating	1x 208-240V 50Hz, 3x 208-240V 50Hz, 3x 380-415V +N 50Hz, 3x 380-415V 50Hz, 3x 440V 60Hz, 3x 480V 50Hz, 3x 480V 60Hz		
GAS OUTPUT (KW)	16,5	19,5	25
ELECTRICAL HEATING			
ELECTRICAL CONNECTION - electric heating	3x 208-240V 50Hz, 3x 380-415V 50Hz, 3x 440V 60Hz, 3x 480V 60Hz		
ENERGY (kW)	13,5	13,5 / 18,0	18,0 / 24,0
STEAM HEATING			
STEAM CONNECTION (NPT)	3/4"	3/4"	3/4"
ELECTRICAL CONNECTION- steam heating	3x220-240V 50Hz, 1x220-240V 50Hz, 3x380-415V 50Hz	1x 208-240V 50Hz, 3x 208-240V 50Hz, 3x 380-415V 50Hz, 3x 440V 60Hz, 3x 480V 50Hz, 3x 480V 60Hz	
STEAM OUTPUT * (kW)	16,6 - 19,4 / 20,0 - 23,3	25,5 - 29,9 / 21,5 - 24,0	25,5 - 35,6 / 24,8 -27,7
STEAM PRESSURE (BAR)	3-6/7-10	3-6/7-10	3-6/7-10
MOTOR			
FAN (KW)	0,55	0,55	0,55
DRIVE (KW)	0,25	0,25	0,25
PROGRAMMER			
EASY CONTROL- antivandal (ECT)	Standard	Standard	Standard
FLEX CONTROL	Available	Available	Available
DIMENSIONS			
H X W X D (MM)	1680 x 795 x 1070	1680 x 795 x 1160	1680 x 795 x 1280
NET WEIGHT (KG)	230	230	240
TRANSPORT DATA			
PACKED H X W X D (MM)	1785 x 855 x 1100	1785 x 855 x 1190	1785 x 855 x 1310
GROSS WEIGHT (KG)	245	250	260

* Steam output is flexible depending on steam pressure, The data concerning dimensions of machines include all extended parts

